

SLIDING PATIO DOOR

INTEGRITY® FROM MARVIN
ALL ULTREX® SERIES

2 Panel Sliding Patio Door

Masonry Opening	5' - 0" (1524)	6' - 0" (1829)
Rough Opening	5' - 0" (1524)	6' - 0" (1829)
Frame Size	4' - 11 1/2" (1511)	5' - 11 1/2" (1816)
Glass Size	26 1/4" (667)	32 1/4" (819)

6' - 7 3/4" (2026)		IFSPD5068XO
6' - 8" (2032)		IFSPD6068XO
6' - 7 1/2" (2019)		
7' - 3 3/4" (1973)		
6' - 9 3/4" (2076)		IFSPD50610XO
6' - 10" (2083)		
6' - 9 1/2" (2070)		IFSPD60610XO
7' - 3 3/4" (1974)		
7' - 11 3/4" (2432)		IFSPD5080XO
8' - 0" (2438)		
7' - 11 1/2" (2426)		IFSPD6080XO
8' - 3 3/4" (2280)		

3 Panel Sliding Patio Door

Masonry Opening	9' - 0" (2743)	9' - 0" (2743)	9' - 0" (2743)
Rough Opening	9' - 0" (2743)	9' - 0" (2743)	9' - 0" (2743)
Frame Size	8' - 11 1/2" (2731)	8' - 11 1/2" (2731)	8' - 11 1/2" (2731)
Glass Size	32 1/4" (819)	32 1/4" (819)	32 1/4" (819)

6' - 9 3/4" (2076)		IFSPD90610XOO
6' - 10" (2083)		
6' - 9 1/2" (2070)		IFSPD90610OOX
7' - 3 3/4" (1924)		IFSPD90610OXO
7' - 11 3/4" (2432)		IFSPD9080XOO
8' - 0" (2438)		
7' - 11 1/2" (2426)		IFSPD9080OOX
8' - 3 3/4" (2280)		IFSPD9080OXO

GBG available in standard Rectangular lite cut, shown.

Details and Elevations not to scale.

XO operation shown, OX operation optional.

MULTIPLE ASSEMBLIES

Multiple assembly units can be factory mulled up to 1 unit wide by 2 units high.

MAXIMUM ROUGH OPENING: not to exceed 72" x 100 1/2". Field mull kits available for up to 3 units wide by 2 units high not to exceed 110" x 112". Structural mullion reinforcement is required for some assemblies.


Please consult your local Integrity representative for more information.

SLIDING PATIO DOOR

Direct Glaze Transom
Over Sliding Patio Door

Masonry Opening	6' - 0" (1829)
Rough Opening	6' - 0" (1829)
Frame Size	5' - 11 1/2" (1816)

8' - 3 3/4" (2534)
8' - 4" (2540)
8' - 3 1/2" (2527)



IFSPDDG6016 / IFSPD60610

Sliding Patio Door
Direct Glaze Transom

Masonry Opening	5' - 0" (1524)	6' - 0" (1829)	9' - 0" (2743)
Rough Opening	5' - 0" (1524)	6' - 0" (1829)	9' - 0" (2743)
Frame Size	4' - 11 1/2" (1511)	5' - 11 1/2" (1816)	8' - 11 1/2" (2731)
Glass Size	57 1/4" (1454)	69 1/4" (1759)	105 1/4" (2673)

1' - 5 3/4" (451)	0' - 11 3/4" (298)
1' - 6" (457)	1' - 0" (305)
1' - 5 1/2" (445)	0' - 11 1/2" (292)
15 1/4" (387)	9 1/4" (235)



IFSPDDG5010



IFSPDDG6010




IFSPDDG9010



IFSPDDG5016



IFSPDDG6016



IFSPDDG9016

GBG available in standard Rectangular lite cut, shown.

Details and Elevations not to scale.

XO operation shown, OX operation optional.

MULTIPLE ASSEMBLIES

Multiple assembly units can be factory mulled up to 1 unit wide by 2 units high.

MAXIMUM ROUGH OPENING: not to exceed 72" x 100 1/2". Field mull kits available for up to 3 units wide by 2 units high not to exceed 110" x 112". Structural mullion reinforcement is required for some assemblies.

Please consult your local Integrity® representative for more information.

SLIDING PATIO DOOR

INTEGRITY® FROM MARVIN
ALL ULTREX® SERIES

Construction Details

